



5405

SAE 140139

Ref. Aeroquip 2040
Ref. Parker FG

Increase and Extension Connectors

5405-①-② ①-MP ②-FP	① Male NPTF	② Female NPTF	C Hex	D Drill	L Length	LL Assembled	Operating Pressure
Increase Connectors							
5405-02-04	1/8 - 27	1/4 - 18	3/4	0.188	1.21	0.98	6,000
5405-02-06	1/8 - 27	3/8 - 18	7/8	0.188	1.29	1.06	6,000
5405-02-08	1/8 - 27	1/2 - 14	1 1/8	0.188	1.50	1.27	5,000
5405-04-06	1/4 - 18	3/8 - 18	7/8	0.281	1.44	1.10	6,000
5405-04-08	1/4 - 18	1/2 - 14	1 1/8	0.281	1.68	1.34	5,000
5405-04-12	1/4 - 18	3/4 - 14	1 3/8	0.281	1.77	1.43	4,000
5405-06-08	3/8 - 18	1/2 - 14	1 1/8	0.406	1.68	1.33	5,000
5405-06-12	3/8 - 18	3/4 - 14	1 3/8	0.406	1.75	1.40	4,000
5405-08-12	1/2 - 14	3/4 - 14	1 3/8	0.531	1.93	1.47	4,000
5405-08-16	1/2 - 14	1 - 11 1/2	1 5/8	0.531	2.18	1.72	3,000
5405-12-16	3/4 - 14	1 - 11 1/2	1 5/8	0.719	2.18	1.70	3,000
5405-12-20	3/4 - 14	1 1/4 - 11 1/2	2"	0.719	2.32	1.84	2,500
5405-16-20	1 - 11 1/2	1 1/4 - 11 1/2	2"	0.938	2.46	1.89	2,500
5405-16-24	1 - 11 1/2	1 1/2 - 11 1/2	2 3/8	0.938	2.54	1.97	2,000
5405-20-24	1 1/4 - 11 1/2	1 1/2 - 11 1/2	2 3/8	1.250	2.50	1.91	2,000
5405-20-32	1 1/4 - 11 1/2	2 - 11 1/2	2 7/8	1.250	2.65	2.06	1,500
5405-24-32	1 1/2 - 11 1/2	2 - 11 1/2	2 7/8	1.500	2.63	2.04	1,500
Extension Connectors							
5405-02-02	1/8 - 27	1/8 - 27	5/8	0.188	1.04	0.81	6,000
5405-04-02	1/4 - 18	1/8 - 27	5/8	0.281	1.00	0.66	6,000
5405-04-04	1/4 - 18	1/4 - 18	3/4	0.281	1.39	1.05	6,000
5405-06-04	3/8 - 18	1/4 - 18	3/4	0.406	1.25	0.90	6,000
5405-06-06	3/8 - 18	3/8 - 18	7/8	0.406	1.44	1.09	6,000
5405-08-04	1/2 - 14	1/4 - 18	7/8	0.531	1.50	1.04	6,000
5405-08-06	1/2 - 14	3/8 - 18	7/8	0.531	1.69	1.23	6,000
5405-08-08	1/2 - 14	1/2 - 14	1 1/8	0.531	1.87	1.41	5,000
5405-12-06	3/4 - 14	3/8 - 18	1 1/8	0.719	1.51	1.03	5,000
5405-12-08	3/4 - 14	1/2 - 14	1 1/8	0.719	1.57	1.09	5,000
5405-12-12	3/4 - 14	3/4 - 14	1 3/8	0.719	1.93	1.45	4,000
5405-16-08	1 - 11 1/2	1/2 - 14	1 3/8	0.719	1.62	1.05	5,000
5405-16-12	1 - 11 1/2	3/4 - 14	1 3/8	0.938	1.94	1.37	4,000
5405-16-16	1 - 11 1/2	1 - 11 1/2	1 5/8	0.938	2.37	1.80	3,000
5405-20-12	1 1/4 - 11 1/2	3/4 - 14	2"	1.250	1.38	0.79	2,500
5405-20-16	1 1/4 - 11 1/2	1 - 11 1/2	2"	1.156	1.91	1.33	2,500
5405-20-20	1 1/4 - 11 1/2	1 1/4 - 11 1/2	2"	1.250	2.49	1.90	2,500
5405-24-20	1 1/2 - 11 1/2	1 1/4 - 11 1/2	2 3/8	1.500	2.26	1.67	2,000
5405-24-24	1 1/2 - 11 1/2	1 1/2 - 11 1/2	2 3/8	1.500	2.53	1.94	2,000
5405-32-32	2 - 11 1/2	2 - 11 1/2	2 7/8	1.938	2.66	2.05	1,500

Safety Factor 4:1

Reducer bushings (5406) & (5406E) are on the next two pages.